Sleeve-It Automatic Shrink Sleeve Applicator

The stainless steel construction Sleeve-It is a versatile and efficient solution for your sleeve applicating needs. Designed to handle bottle sizes ranging from 10 to 75 mm, Sleeve-It is capable of processing up to 130 bottles per minute, ensuring dependable and steady-state production. Whether you require neckbanding or full body sleeves, this advanced applicator meets your demands with precision and reliability. Sleeve-It offers the option of vertical perforation, providing easy-to-tear sleeves for consumer convenience. Enhance your packaging efficiency and product presentation with the Shrink Sleeve Applicator "Sleeve-It."

Features

- Stainless Steel Frame
- Safety Interlocks
- Casters & Leveling Pads
- Bottle Spacing Wheel
- Integrated PLC control panel for easy adjustment.
- 7" touchscreen HMI with Bilingual Operation (ENG/SPA)
- Quick and simple product changeover
- Low Material Sensor with Stacklight
- Left to Right Direction

Optional Features

- Vertical Perforator
- Print Registration
- Straight-Sided Bottle System
- Right to Left Direction
- Inspection/Reject Vision System
- Fallen Bottle Sensors (In/Out)

Film Width Range - Layflat	25 mm-120 mm
Film Height Range	Up to 10"
Container Height	Up to 10"
Line Speed*	Up to 130 bottles/minute
Roll Capacity	OD of 17"
Core Diameter	5"
Max OD of roll	17"
Electrical Requirements	230 V / 3 PH / 60 hZ / 25 Amps
Pneumatic Requirements	90 PSI at 5 CFM
Overall Machine Dimensions	30.4" L x 19.39" D Height: 62"-80"

^{*}Line speed varies depending on the sleeve size.

