

Step-by-Step Installation Guide for Nitrous Flush Option on 3000 Band Sealer

Video Tutorial:

[Installation of CE-1085 Nitro Flush Kit - YouTube](#)

This guide will walk you through installing the nitrous flush option on your 3000 band sealer by replacing the existing handles with the provided nitrous flush box guide. Follow these steps carefully for a successful installation.

1. Gather Your Tools and Materials

- **Nitrous flush box guide** (provided)
- **Set of bolts and plate** (included for securing the guide)
- **Long screwdriver** (longest available for easier access)
- **14 mm wrench or socket** (for tightening bolts)

2. Remove the Existing Handles

- **Go inside the machine:**
 - **For newer models:** Find the clips (top and bottom). Push them in to release and pop out the handles.
 - **For older models:** Locate the screw on the side. Loosen it to release the clamp, then remove the handles.
 - - **Locate the two screws** holding the current handles on the outside of the machine.
 - - **Loosen and remove** these screws using the screwdriver. Set them aside.

3. Position the Nitrous Flush Box Guide

- **Place the guide** where the old handles were removed.
- **Align it** so the tube will go inside the bag during operation (adjust depth as needed for your bags).
- **Insert the bolts** through the guide and the machine's frame from the outside.



Cleveland Equipment

866-888-6327

sales@clevelandequipme

www.clevelandequipme

Step-by-Step Installation Guide for Nitrous Flush Option on 3000 Band Sealer

Video Tutorial:

[Installation of CE-1085 Nitro Flush Kit - YouTube](#)

4. Secure the Guide

- **Inside the machine:** Place the provided plate over the bolts to act as a large washer for support. **Note:** You will only use two of the bolt holes for this installation. Use the bottom set of holes on the plate.
- **Thread the nuts** onto the bolts. Start with one bolt to hold the guide in place, then add the second.
- **Tighten the bolts** using the 14 mm wrench or socket. Ensure it's secure but avoid overtightening.
- **Important: The flush mechanism must line up with the bag guide.** This is the most critical part of the installation—double-check this alignment before final tightening to ensure proper operation.

5. Check Alignment

- **Verify the tube's position:** It should extend into the bag when a bag is placed on the guide.
- **Adjust if necessary** to ensure the bag slides on properly and the tube fits inside.

6. Connect the Hose

- **Attach the hose** to the tube on the nitrous flush box guide.
- **Connect the other end** to your nitrous supply regulator (sourced from your supplier).

7. Test the Installation

- **Place a bag** on the guide to confirm it fits correctly and the tube goes inside.
- **Check the system:** Ensure everything is secure and ready for nitrous flush operation.

Key Tips

- Use the longest screwdriver available to make screw removal and installation easier.
- Start with one bolt when securing the guide to keep it steady while you align the second.
- Double-check alignment, as **the flush mechanism lining up with the bag guide** is essential for success.



Cleveland Equipment

866-888-6327

sales@clevelandequipme

www.clevelandequipme