

# S-7 Dual-Lane Weigh Filler



EQUIPMENT & MACHINERY COMPANY

www.clevelandequipment.com

866-888-6327

- Two lanes for twice the speed
- Self-adjusting controller
- Reads out to 1 gram or .001 lb
- Controller range up to 10 lbs.
- Supply hopper 5.1 cu. ft.
- Powder-coated chassis. Stainless steel optional
- Footprint 7.5 sq ft, 68" high
- 120V 60Hz (wall outlet) 240V 50Hz option available
- Handles any dry bulk from powders to large parts
- Compatible with all bags, rigid containers and bagging machines
- Automatic tare adjustment
- Self adjusting bulk & dribble speed control
- 600-1200 fills/hour

## Information:

The model S-7 two lane net weigher share many of the same basic characteristics of the S-4. A very accurate and easy to use Logical Controller II allows for three different modes of operation. In simultaneous dump the machine fills both weigh hoppers at the same time, allowing for twice as much product flow than our S-4. In individual dump the machine dumps whichever weigh hopper is at weight. This gives twice the speed of our S-4 machine. Finally the model S-7 can mix products. The Logical Controller II can be set to weigh two completely different products at different weights to easily mix products into a container.



## Specifications:

- Overall height: 5'8" (68"), occupies only 30"x34" of floor space
- Hopper size: 36" x 24" (5.1 cu. ft. product capacity)
- Scale total weight 225 lbs.
- Standard funnel size: 2.5" x 2.5"
- Power requirements: 4 amps, 120 volts 60Hz AC
- Air Requirements: <1 CFM air supply at 30 psi
- One year limited Warranty
- Standard S-7 Options
  - Fill spouts
  - Divided supply hopper
  - 240v 50Hz AC
  - Stainless steel chassis